

easiMARK Colourprint Plus

product specification



garment film

White matt PVC media for use on eco and true solvent printers for heat transfer applications.

advantages

- Soft very thin film (160 microns)
- Easy weeding
- Ideal for both large & small detailed transfers
- Suitable for cotton, polyester, acrylic & similar fibres
- No curling - use of application tape optional
- Excellent print quality
- Supplied by the metre at 500mm and 750mm wide

application advice

print & cutting	heat pressing
<ul style="list-style-type: none"> • Print your image positive following the instruction of the printer manufacturer. • Please take note of the printing (45°C) and drying temperatures (50°C). • Use the appropriate printing profile (for instance, with Roland, select Colorip or Versawork, and then profile TTRH, textile). • Remove the Colourprint from the printer and wait for the inks to dry at room temperature for at least 4 hours. 	<ul style="list-style-type: none"> • Weed the excess material. • Using an application tape is not compulsory to transfer the image. It is possible to transfer the image by hand or with a polyester application tape. • Position and heat press the image on the garment protected by a silicone paper at 160°C for 20 seconds - medium pressure. • Peel the application tape off when cold.

recommendations

Printable media is very sensitive: always handle with care, with clean hands.
 Always store the roll in a plastic bag protected from dust.
 It is important to always use OEM inks from the printer manufacturer.
 These recommendations are based on our own experiences.
 We always recommend testing before starting standard production.
 Store roll vertically, one year in a dry room (15 - 25°C), protected from sunlight.

Always read the instructions mentioned on the garment.
 After heat pressing, wait 24 hours before the first wash.



Wash inside out without bleach or any aggressive washing products.